

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims:

1. (Currently amended) An electronic apparatus ~~comprises~~comprising:
a light emitting element[[,]];
a color filter provided in either side of an anode or a cathode of the light emitting element[[,]]; and
two polarizers sandwiching the light emitting element and the color filter,
wherein the anode and the cathode transmit light,
wherein deflection angles of the two polarizers are different from each other, and
wherein light obtained from the light emitting element is white.
2. (Currently amended)-~~In the~~ An electronic apparatus ~~of~~according to claim 1, wherein the light emitting element comprises a first light emitting layer which exhibits blue emission and a second light emitting layer dispersed with a phosphorescent material with a concentration of 10 wt % or more in a host material, and exhibiting both phosphorescence from the phosphorescent material and emission from the phosphorescent material in the excimer state.
3. (Currently amended)-~~In the~~ An electronic apparatus ~~of~~according to claim 2, wherein the highest peak in the emission spectrum of the first light emitting layer is located in the region from 400 nm to 500 nm.
4. (Currently amended)-~~In the~~ An electronic apparatus ~~of~~according to claim 2, wherein the phosphorescent material exhibits emission having two or more peaks in the region from 500 nm to 700 nm, and one of the two or more peaks corresponds to the excimer emission.

5. (Currently amended) ~~In the~~ An electronic apparatus ~~of~~ according to claim 1, wherein the electronic apparatus is used in a portable information terminal, a portable phone, or an electronic book.

6. (Currently amended) An electronic apparatus ~~comprises~~ comprising:
a light emitting element~~[[,]]~~;
two color filters sandwiching the light emitting element~~[[,]]~~; and
two polarizers sandwiching the light emitting element and the two color filters,
wherein the an anode and the a cathode transmit light,
wherein deflection angles of the two polarizers are different from each other, and
wherein light obtained from the light emitting element is white.

7. (Currently amended) ~~In the~~ An electronic apparatus ~~of~~ according to claim 6, wherein the light emitting element comprises a first light emitting layer which exhibits blue emission and a second light emitting layer dispersed with a phosphorescent material with a concentration of 10 wt % or more in a host material, and exhibiting both phosphorescence from the phosphorescent material and emission from the phosphorescent material in the excimer state.

8. (Currently amended) ~~In the~~ An electronic apparatus ~~of~~ according to claim 7, wherein the highest peak in the emission spectrum of the first light emitting layer is located in the region from 400 nm to 500 nm.

9. (Currently amended) ~~In the~~ An electronic apparatus ~~of~~ according to claim 7, wherein the phosphorescent material exhibits emission having two or more peaks in the region from 500 nm to 700 nm, and one of the two or more peaks corresponds to the excimer emission.

10. (Currently amended)~~In the~~ An electronic apparatus ~~of~~ according to claim 6, wherein the electronic apparatus is used in a portable information terminal, a portable phone, or an electronic book.

11. (Currently amended) An electronic apparatus ~~comprises~~ comprising:
a light emitting element~~[[,]]~~;
a first transistor for determining a current value supplied to the light emitting element~~[[,]]~~;
a second transistor for selecting emission or non-emission of the light emitting element~~[[,]]~~;
a color filter provided in either side of an anode or a cathode of the light emitting element~~[[,]]~~; and
two polarizers sandwiching the light emitting element and the color filter,
wherein the anode and the cathode transmit light,
wherein deflection angles of the two polarizers are different from each other,
wherein light obtained from the light emitting element is white,
wherein ~~the light emitting element~~, the first transistor~~[[,]]~~ and the second transistor are connected in series between a first power supply and ~~a second power supply~~ the light emitting element, and
wherein a gate of the first transistor is connected to ~~a third~~ the first power supply.

12. (Currently amended)~~In the~~ An electronic apparatus ~~of~~ according to claim 11, wherein the light emitting element comprises a first light emitting layer which exhibits blue emission and a second light emitting layer dispersed with a phosphorescent material with a concentration of 10 wt % or more in a host material, and exhibiting both phosphorescence from the phosphorescent material and emission from the phosphorescent material in the excimer state.

13. (Currently amended)~~In the~~ An electronic apparatus ~~of according to~~ claim 12, wherein the highest peak in the emission spectrum of the first light emitting layer is located in the region from 400 nm to 500 nm.

14. (Currently amended)~~In the~~ An electronic apparatus ~~of according to~~ claim 12, wherein the phosphorescent material exhibits emission having two or more peaks in the region from 500 nm to 700 nm, and one of the two or more peaks corresponds to the excimer emission.

15. (Currently amended)~~In the~~ An electronic apparatus ~~of according to~~ claim 11, wherein the electronic apparatus is used in a portable information terminal, a portable phone, or an electronic book.

16. (Currently amended)An electronic apparatus comprises~~comprising~~:
a light emitting element~~[[,]]~~;
a first transistor for determining a current value supplied to the light emitting element~~[[,]]~~;
a second transistor for selecting emission or non-emission of the light emitting element~~[[,]]~~;
two color filters sandwiching the light emitting element~~[[,]]~~; and
two polarizers sandwiching the light emitting element and the two color filters,
wherein the an anode and the a cathode transmit light,
wherein deflection angles of the two polarizers are different from each other,
wherein light obtained from the light emitting element is white,
wherein the light emitting element, the first transistor~~[[,]]~~ and the second transistor are connected in series between a first power supply and ~~a second power supply~~ the light emitting element, and
wherein a gate of the first transistor is connected to ~~a third~~ the first power supply.

17. (Currently amended)~~In the~~ An electronic apparatus ~~of~~ according to claim 16, wherein the light emitting element comprises a first light emitting layer which exhibits blue emission and a second light emitting layer dispersed with a phosphorescent material with a concentration of 10 wt % or more in a host material, and exhibiting both phosphorescence from the phosphorescent material and emission from the phosphorescent material in the excimer state.

18. (Currently amended)~~In the~~ An electronic apparatus ~~of~~ according to claim 17, wherein the highest peak in the emission spectrum of the first light emitting layer is located in the region from 400 nm to 500 nm.

19. (Currently amended)~~In the~~ An electronic apparatus ~~of~~ according to claim 17, wherein the phosphorescent material exhibits emission having two or more peaks in the region from 500 nm to 700 nm, and one of the two or more peaks corresponds to the excimer emission.

20. (Currently amended)~~In the~~ An electronic apparatus ~~of~~ according to claim 16, wherein the electronic apparatus is used in a portable information terminal, a portable phone, or an electronic book.

21. (Currently amended)~~An electronic apparatus comprises~~ comprising:
a light emitting element~~[[,]]~~;
a color filter provided in either side of an anode or a cathode of the light emitting element~~[[,]]~~; and
two liquid crystal panels sandwiching the light emitting element and the color filter,
wherein the anode and the cathode transmit light, and
wherein light obtained from the light emitting element is white.

22. (Currently amended)~~In the~~ An electronic apparatus ~~of~~ according to claim 21, wherein the light emitting element comprises a first light emitting layer which exhibits blue emission and

a second light emitting layer dispersed with a phosphorescent material with a concentration of 10 wt % or more in a host material, and exhibiting both phosphorescence from the phosphorescent material and emission from the phosphorescent material in the excimer state.

23. (Currently amended)~~In the~~ An electronic apparatus ~~of~~ according to claim 22, wherein the highest peak in the emission spectrum of the first light emitting layer is located in the region from 400 nm to 500 nm.

24. (Currently amended)~~In the~~ An electronic apparatus ~~of~~ according to claim 22, wherein the phosphorescent material exhibits emission having two or more peaks in the region from 500 nm to 700 nm, and one of the two or more peaks corresponds to the excimer emission.

25. (Currently amended)~~In the~~ An electronic apparatus ~~of~~ according to claim 21, wherein the electronic apparatus is used in a portable information terminal, a portable phone, or an electronic book.

26. (Currently amended)An electronic apparatus ~~comprises~~comprising:
a light emitting element~~[[,]]~~;
two color filters sandwiching the light emitting element~~[[,]]~~; and
two liquid crystal panels sandwiching the light emitting element and the two color filters~~[[,]]~~;
wherein the an anode and the a cathode transmit light, and
wherein light obtained from the light emitting element is white.

27. (Currently amended)~~In the~~ An electronic apparatus ~~of~~ according to claim 26, wherein the light emitting element comprises a first light emitting layer which exhibits blue emission and a second light emitting layer dispersed with a phosphorescent material with a concentration of 10

wt % or more in a host material, and exhibiting both phosphorescence from the phosphorescent material and emission from the phosphorescent material in the excimer state.

28. (Currently amended)~~In the~~ An electronic apparatus ~~of according to~~ claim 27, wherein the highest peak in the emission spectrum of the first light emitting layer is located in the region from 400 nm to 500 nm.

29. (Currently amended)~~In the~~ An electronic apparatus ~~of according to~~ claim 27, wherein the phosphorescent material exhibits emission having two or more peaks in the region from 500 nm to 700 nm, and one of the two or more peaks corresponds to the excimer emission.

30. (Currently amended)~~In the~~ An electronic apparatus ~~of according to~~ claim 26, wherein the electronic apparatus is used in a portable information terminal, a portable phone, or an electronic book.

31. (Currently amended)An electronic apparatus ~~comprises~~comprising:
a light emitting element~~[[,]]~~;
a first transistor for determining a current value supplied to the light emitting element~~[[,]]~~;
a second transistor for selecting emission or non-emission of the light emitting element~~[[,]]~~;
a color filter provided in either side of an anode or a cathode of the light emitting element~~[[,]]~~; and
two liquid crystal panels sandwiching the light emitting element and the color filter,
wherein the anode and the cathode transmit light,
wherein light obtained from the light emitting element is white,

wherein ~~the light emitting elements,~~ the first transistor[[,]] and the second transistor are connected in series between a first power supply and ~~a second power supply~~ the light emitting element, and

wherein a gate of the first transistor is connected to ~~a third~~ the first power supply.

32. (Currently amended)~~In the~~ An electronic apparatus ~~of according to~~ claim 31, wherein the light emitting element comprises a first light emitting layer which exhibits blue emission, and a second light emitting layer dispersed with a phosphorescent material with a concentration of 10 wt % or more in a host material, and exhibiting both phosphorescence from the phosphorescent material and emission from the phosphorescent material in the excimer state.

33. (Currently amended)~~In the~~ An electronic apparatus ~~of according to~~ claim 32, wherein the highest peak in the emission spectrum of the first light emitting layer is located in the region from 400 nm to 500 nm.

34. (Currently amended)~~In the~~ An electronic apparatus ~~of according to~~ claim 32, wherein the phosphorescent material exhibits emission having two or more peaks in the region from 500 nm to 700 nm, and one of the two or more peaks corresponds to the excimer emission.

35. (Currently amended)~~In the~~ An electronic apparatus ~~of according to~~ claim 31, wherein the electronic apparatus is used in a portable information terminal, a portable phone, or an electronic book.

36. (Currently amended)An electronic apparatus ~~comprises~~comprising:
a light emitting element[[,]];
a first transistor for determining a current value supplied to the light emitting element[[,]];

a second transistor for selecting emission or non-emission of the light emitting element[[,]]; and

two color filters sandwiching the light emitting element[[,]]; and
two liquid crystal panels sandwiching the light emitting element and the two color filters,
wherein the an anode and the a cathode transmit light,
wherein light obtained from the light emitting element is white,
wherein the light emitting element, the first transistor[[,]] and the second transistor are
connected in series between a first power supply and a second power supply the light emitting
element, and

wherein a gate of the first transistor is connected to a third the first power supply.

37. (Currently amended) ~~In the~~ An electronic apparatus ~~of according to~~ claim 36, wherein the light emitting element comprises a first light emitting layer which exhibits blue emission and a second light emitting layer dispersed with a phosphorescent material with a concentration of 10 wt % or more in a host material, and exhibiting both phosphorescence from the phosphorescent material and emission from the phosphorescent material in the excimer state.

38. (Currently amended) ~~In the~~ An electronic apparatus ~~of according to~~ claim 37, wherein the highest peak in the emission spectrum of the first light emitting layer is located in the region from 400 nm to 500 nm.

39. (Currently amended) ~~In the~~ An electronic apparatus ~~of according to~~ claim 37, wherein the phosphorescent material exhibits emission having two or more peaks in the region from 500 nm to 700 nm, and one of the two or more peaks corresponds to the excimer emission.

40. (Currently amended) ~~In the~~ An electronic apparatus ~~of according to~~ claim 36, wherein the electronic apparatus is used in a portable information terminal, a portable phone, or an electronic book.

Applicant : Hiroko Abe et al.
Serial No. : 10/816,185
Filed : April 2, 2004
Page : 12 of 13

Attorney's Docket No.: 12732-222001 / US7082

Amendments to the Drawings:

Please substitute the attached drawings in English for the drawings submitted with the application.